
ISSN 2979 - 1995

Journal of Engineering-Themed Environmental Tourism



VOLUME 1
ISSUE 2
SEPTEMBER 2026

PUBLISHED BY FAITH CONGLOMERATE LIMITED



CIVIL & ENVIRONMENTAL ENGINEERING CONSULTANTS

UNITED KINGDOM

www.fcl-uk.com

JOURNAL OF ENGINEERING-THEMED ENVIRONMENTAL TOURISM



VOLUME 1 , ISSUE 2

TABLE OF CONTENTS

Editorial

Welcome to JETET: The New Frontier of Engineering Tourism ..... Page 5

Research

Research Paper: Sustainable Landscape Reclamation of Granite Quarries:..... Page 8

Expert Interview

Q & A INTERVIEW : MICHAEL MAINELLI ..... Page 37

Opinion Piece

ENGINEERING THE COEXISTENCE OF TOURISM AND OIL EXPLORATION INDUSTRIES..... Page 51

Announcements

Call for Papers: Volume 1, Issue 3 (December 30, 2026) ..... Page 62

Sponsorships & Partnerships.: Future Volumes .....Page 67

EDITORIAL

WELCOME TO THE JOURNAL OF ENGINEERING -THEMED ENVIRONMENTAL TOURISM.

I am delighted and honoured to welcome you to the second issue of the



Gbemisola Agbaje
Editor-in-Chief

Journal Of Engineering-Themed Environmental Tourism.

I am Gbemisola Arike Agbaje, the Editor-In Chief and the progenitor of engineering-themed environmental tourism.

I am a Chartered Professional in the fields of Civil Engineering and Environmental Engineering. I am a Tourism enthusiast, Nature enthusiast, and a Space enthusiast. I am also certified in Systems Safety Engineering.

The Energy and Tourism Industries are massive, with resulting environmental and engineering implications and effects on the sustainability of habitats across the Earth. In this issue , Engineering Resilience in Modern Global Tourism is a topic of interest. The Tourism Industry has evolved simultaneously with rapid advances in the Engineering Field.

Volume 1 , Issue 2, , includes the following ,

1. Sustainable Landscape Reclamation of Granite Quarries: Environmental Impacts, Restoration Strategies, and Strategic Study Analysis from Guntur, India
2. Expert Interview with Michael Maenelli, Chairman of Z/Yen , President of London Chamber of Commerce , former Lord Mayor of London

I invite you to network with JETET through our Social Media Networking page on LinkedIn by joining the JETET Group on LinkedIn.

Our LinkedIn Group, JETET can be found here
LinkedIn

Our Website is https://www.journalofengineering-themedenvironmentaltourism.org

Here you can find our Call for Papers and our Author Guidelines.

Subscribe to our YouTube Channel

Our contact details are also available on our website, and we have a dedicated page on the website of Faith Conglomerate Limited

https://www.fcl-uk.com/jetet

We are continuously building our Editorial Board, so if you are interested in volunteering on our Editorial Board, please contact us. We accept Academia ,Students, Researchers and Seasoned Experts to our Editorial Board.

We invite both local and international Researchers, Industry Experts, Practitioners , PhD Candidates and Undergraduates with relevant experience in Tourism , Engineering and Sustainability and Space and Astro-Travel , to publish their relevant research papers, articles or opinion pieces in our Journal.

We welcome Sponsorship Proposals for future Publications from parties relevant to our areas of interest.

JETET is published by Faith Conglomerate Limited, UK and is an e-Journal.

I really hope you enjoy reading Volume 1, Issue 2 and welcome feedback

Yours,

Gbemi

Editor-In-Chief

RESEARCH

In this Issue

1. ***Peer Reviewed*** Research Paper *Sustainable Landscape Reclamation of Granite Quarries: Environmental Impacts, Restoration Strategies, and Strategic Study Analysis from Guntur, India*

RESEARCH PAPER

(PEER REVIEWED)

Research Paper Topic:

Sustainable Landscape Reclamation of Granite Quarries: Environmental Impacts, Restoration Strategies, and Strategic Study Analysis from Guntur, India

Sustainable Landscape Reclamation of Granite Quarries: Environmental Impacts, Restoration Strategies, and Strategic Study Analysis from Guntur, India

Surendra Babu Gantenapati
Bowling Green State University
Bowling Green, Ohio, United States sbgantenapati@gmail.com
https://orcid.org/0009-0008-4748-4248

Lavanya Vemula
University of North Carolina at Charlotte
Charlotte, NC, United States
ar.lavanya.v@gmail.com
https://orcid.org/0009-0007-0182-1889

Abstract— Granite quarrying supplies essential construction materials but causes persistent changes to landform, soil, vegetation, hydrology, biodiversity, and landscape character. This study develops an integrated framework for sustainable quarry reclamation by combining a structured narrative review with an illustrative spatial case study of a granite quarry landscape in Guntur District, Andhra Pradesh, India. The review synthesizes evidence concerning mine-land disturbance, slope stabilization, soil rehabilitation, revegetation, water management, and post-quarry adaptive reuse. The case study integrates field observations and geographic information system analysis of topography, relief, slope, drainage, soil conditions, land use, vegetation indices, and potential surface-water features. Unlike traditional reclamation approaches that often treat engineering stabilization, soil treatment, and revegetation as separate closure measures, the proposed framework connects environmental diagnosis, spatial-priority zoning, ecological restoration, community-oriented ecotourism, and long-term performance monitoring within an adaptive sequence. The findings demonstrate that effective reclamation cannot be reduced to planting or site beautification alone. Stable landform design, runoff and sediment control, recovery or reconstruction of growth media, staged establishment of native vegetation, and a feasible post-quarry use must be planned as coordinated interventions. The Guntur case demonstrates how steep quarry faces, disconnected drainage, exposed rock, waste deposits, and localized water accumulation constrain restoration, while remnant vegetation, surrounding agricultural land, and pit-water storage provide opportunities for ecological recovery, environmental education, and controlled ecotourism. A five-phase framework is proposed comprising site assessment and planning, stabilization and risk control, hydrological and soil recovery, ecological restoration, and ecotourism development with adaptive monitoring. The study contributes a transferable strategic planning structure for landscape architects, quarry operators, regulators, and communities addressing abandoned or closing hard-rock quarries.

Keywords—Granite quarrying; mine reclamation; ecological restoration; revegetation; slope stabilization; GIS; post-mining land use

Acronym—Digital Elevation Model (DEM), Geographic Information System (GIS), Universal Transverse Mercator (UTM), World Geodetic System 1984 (WGS 84), European Petroleum Survey Group (EPSG) code, Linear Imaging Self-Scanning Sensor III (LISS-III), Land Use / Land Cover (LULC), Environmental Impact Assessment (EIA), Mines and Minerals (Development and Regulation) (MMDR) Act, District Mineral Foundation (DMF), State Environment Impact Assessment Authority (SEIAA), Andhra Pradesh Pollution Control Board (APPCB), Ministry of Environment, Forest and Climate Change (MoEFCC), Key Performance Indicator (KPI), National Remote Sensing Centre (NRSC), Indian Space Research Organisation (ISRO), Normalized Difference Vegetation Index (NDVI), Normalized Difference Water Index (NDWI)

I. Introduction

Mineral extraction is fundamental to construction and infrastructure development, yet surface mining produces some of the most visible and persistent transformations of terrestrial landscapes. Granite quarrying removes vegetation and topsoil, fragments rock through drilling and blasting, creates benches and steep pit walls, deposits waste material, alters drainage pathways, and generates dust, noise, and traffic. Although dimension-stone operations may produce fewer processing emissions than some other forms of mineral extraction, their cumulative effects on habitat, landform, hydrology, and landscape character can be substantial when closure and reclamation are delayed or inadequately funded (Ashmole and Motloung, 2008; Worlanyo and Jiangfeng, 2021).

The reclamation challenge is not simply to conceal or revegetate an abandoned excavation. A quarry functions as a coupled landscape system in which geomorphology, soil, water, vegetation, biodiversity, public safety, community needs, and future land use interact. Steep slopes restrict soil retention and planting; disrupted drainage accelerates erosion and sediment transport; poor growth media limit vegetation establishment; contaminated or inadequately managed pit water constrains reuse; and an unrealistic post quarry program can undermine long-term maintenance. Effective reclamation therefore requires a coordinated sequence of engineering, ecological, hydrological, and spatial-planning decisions rather than a single treatment applied at closure (Gray and Sotir, 1996; Lottermoser, 2010).

Previous mine-restoration research has examined natural succession, technical reclamation, revegetation, and engineered stabilization. Natural recovery can produce locally adapted plant communities but may proceed slowly on compacted, nutrient-

poor, saline, or physically unstable substrates. Active interventions can accelerate stabilization but may fail when inappropriate species, excessive grading, or uniform soil treatments disregard local site variability (Bradshaw, 1997; Tordoff et al., 2000; Navarro-Ramos et al., 2022).

Traditional reclamation approaches have commonly emphasized regulatory closure, slope stabilization, soil replacement, drainage control, and vegetation establishment. Although these measures are essential, they are frequently planned as separate technical actions and may provide limited guidance for spatial prioritization, community participation, adaptive management, and viable long-term land use. In particular, revegetation or site beautification alone may not resolve persistent safety, hydrological, ecological, and management constraints.

In contrast, this study develops an integrated, phased, and performance-based framework that connects literature-based evidence, field observations, GIS-based environmental diagnosis, engineering stabilization, hydrological and soil recovery, ecological restoration, spatial-priority zoning, community-oriented ecotourism, and long-term monitoring. The framework treats reclamation as an adaptive process in which monitoring can trigger renewed stabilization, drainage modification, soil treatment, planting, or visitor management measures. Its contribution is therefore not a single restoration technique but a coordinated planning structure linking environmental recovery with feasible post-quarry use.

This paper addresses the identified need through two connected components: a structured narrative review of international reclamation principles and an illustrative spatial case study of a granite quarry landscape in Guntur District, Andhra Pradesh, India. The study has four objectives: (1) identify the principal pathways through which granite quarrying affects landform, soil, vegetation, hydrology, biodiversity, and landscape character; (2) compare engineering, hydrological, and ecological reclamation measures; (3) integrate field observations and GIS-derived spatial evidence to identify restoration constraints and opportunities; and (4) propose a phased framework linking stabilization, ecological recovery, spatial-priority zoning, community-oriented ecotourism, and adaptive monitoring.

The proposed framework is intended as a strategic planning tool rather than a construction-ready landscape architectural or engineering design. Detailed geotechnical, hydrogeological, ecological, contamination, visitor-capacity, and socioeconomic investigations would therefore be required before site-level implementation.

II. Materials and Methods

A. Research design

This study adopted a mixed-methods research design that integrates qualitative environmental assessment, Geographic Information System (GIS)-based spatial analysis, field observations, and an extensive review of peer-reviewed literature to develop a comprehensive framework for sustainable granite quarry reclamation. The research combines descriptive, analytical, and case study approaches to evaluate the environmental impacts of granite quarrying and identify effective ecological restoration strategies suitable for post-mining landscapes.

The study was structured around a representative granite quarry located near Phirangipuram, Guntur District, Andhra Pradesh, India, selected because it exhibits the typical environmental conditions associated with abandoned hard-rock quarries, including steep excavated slopes, exposed bedrock, waste rock dumps, disrupted drainage systems, degraded vegetation cover, and altered landforms. This site provided an appropriate setting for investigating the interactions between quarry operations and the surrounding ecological landscape.

A case study methodology was employed to examine site-specific environmental characteristics through the integration of spatial datasets, topographic information, field documentation, and environmental observations. GIS-based analyses were used to evaluate land-use patterns, topography, slope characteristics, relief, vegetation distribution, hydrological networks, groundwater conditions, and flood susceptibility. These spatial datasets were interpreted collectively to identify environmentally sensitive areas, restoration constraints, and opportunities for ecological rehabilitation.

To complement the spatial analysis, a structured narrative literature review was undertaken to synthesize current knowledge on quarry reclamation, ecological restoration, slope stabilization, soil rehabilitation, revegetation, water management, and sustainable post-mining land-use planning. Unlike a formal systematic review, the literature synthesis was designed to identify established engineering and ecological restoration principles that could be integrated with the findings from the Guntur case study. The reviewed literature was critically analyzed to compare international reclamation practices and assess their applicability to granite quarry environments.

The research followed four sequential stages:

- Environmental baseline assessment, including site reconnaissance, field observations, and collection of spatial datasets;


- GIS-based spatial analysis to evaluate terrain characteristics, vegetation condition, hydrology, soil distribution, and environmental constraints;
- Literature synthesis and comparative analysis to identify internationally recognized quarry reclamation strategies and best management practices; and
- Development of an integrated reclamation framework combining engineering stabilization measures, ecological restoration principles, landscape planning, and adaptive post-mining land-use strategies.

This integrated research design enabled the study to evaluate environmental degradation from multiple perspectives while developing a practical, science-based reclamation framework that can be adapted to similar granite quarry landscapes worldwide. The approach also supports sustainable mine closure planning by integrating engineering, ecological, and landscape architectural principles within a unified decision-making framework

B. Framework

The evidence base comprises publications on dimension-stone environmental management, post-mining land use, mine-waste rehabilitation, active revegetation, slope bioengineering, soil salinity and alkalinity, hydrological disturbance, and quarry adaptive reuse. They directly informed at least one of five analytical themes: disturbance pathways, landform stability, soil and growth-media rehabilitation, vegetation establishment, or post-mining use. Foundational books and peer-reviewed articles were used alongside an industry proceedings paper where it provided quarry-specific operational context. The synthesis distinguishes findings supported by published literature from observations derived from the Guntur case material.

FLOW DIAGRAM 1: : BIOLOGICAL-TO-URBAN AI MAPPING ACROSS FIVE REFERENCE SYSTEMS



The methodology integrates three complementary evidence sources: literature and policy review, field investigation, and GIS based spatial analysis. The literature review identifies established quarry-reclamation practices, comparable case studies, relevant scientific evidence, and government requirements. Field investigation records existing vegetation, water conditions, exposed rock surfaces, access, safety hazards, surrounding land uses, and community priorities. GIS and remote-sensing analysis evaluates elevation, slope, drainage, vegetation condition, potential surface water, land use, and site accessibility.

The two evidence streams are consolidated into an integrated database and used to diagnose environmental constraints and opportunities. The results inform spatial-priority zoning for ecological restoration, safety and restricted areas, and controlled ecotourism and interpretation. These zones guide the five-phase reclamation framework covering assessment, stabilization, hydrological and soil recovery, ecological restoration, and ecotourism development. Monitoring provides feedback for adaptive management and may trigger renewed stabilization, drainage improvement, soil treatment, planting, or visitor-control measures.

B.1 Indian Government Policy Context Through 2026

As of August 2026, quarry reclamation in India is governed by a combination of central environmental legislation, national restoration policies, state mineral rules, environmental-clearance conditions, and District Mineral Foundation programmes.

At the central level, the Mines and Minerals (Development and Regulation) Act, 1957 remains the principal mineral-governance legislation. The MMDR Amendment Act, 2025 expanded provisions relating to mineral exploration and development but did not replace existing environmental-clearance or mine-closure requirements (Ministry of Mines Annual Report 2025–26). Environmental appraisal continues under the EIA Notification, 2006, as amended, which requires prior environmental clearance for mining projects and categorises projects for central- or state-level appraisal (EIA Notification Compendium).

The National Action Programme to Combat Desertification, updated in 2023, supports India's commitment to restore 26 million hectares of degraded land by 2030. Quarry reclamation contributes to this objective through soil recovery, erosion control, vegetation establishment, and restoration of ecosystem functions (MoEFCC, 2023).

The Green Credit Rules, 2023, followed by the tree-plantation methodology issued in 2024, introduced incentives for plantation on identified degraded lands. However, green credits are based mainly on verified tree establishment and should not be considered a substitute for mandatory quarry reclamation, native biodiversity recovery, soil development, water management, or long-term vegetation survival (MoEFCC, 2024).

India's updated National Biodiversity Strategy and Action Plan, released in 2024, promotes ecosystem-based restoration, recovery of degraded landscapes, community participation, biodiversity conservation, and coordination among government institutions. This supports a quarry-reclamation approach based on native ecosystems rather than plantation numbers alone (PIB–MoEFCC, 2024).

The revised Pradhan Mantri Khanij Kshetra Kalyan Yojana guidelines issued in January 2024 strengthened the use of District Mineral Foundation funds in mining-affected areas. Environmental preservation, pollution control, water management, health, livelihoods, and community development are identified as priority areas. At least 70% of DMF expenditure is directed toward directly affected areas and high-priority sectors (Ministry of Mines, 2024). These funds could support drainage restoration, dust control, waterbody improvement, native planting, and community amenities around Phirangipuram.

The State Mining Index and Mining-Sector Reform Guidelines introduced during 2024–2026 encourage states to establish progressive and final closure plans, financial assurance, mine-closure monitoring, environmental star ratings, water conservation, waste management, and inspection systems for minor-mineral mines. These guidelines represent national policy direction and incentives for state reform; they should not be described as standalone statutory closure requirements (Ministry of Mines, 2025).

At the Andhra Pradesh level, granite, building stone, and road metal are regulated as minor minerals. Quarry leases continue to be administered under the Andhra Pradesh Minor Mineral Concession Rules, 1966, as amended. These rules operate together with approved mining plans, progressive mine-closure plans, lease conditions, and inspections by the Department of Mines and Geology (Andhra Pradesh Mines and Geology).

Environmental clearance is processed through SEIAA Andhra Pradesh, while the Andhra Pradesh Pollution Control Board administers applicable consent and pollution-control requirements. Recent 2026 EIA documents for Andhra Pradesh granite quarries continue to require operation according to approved mining and progressive mine-closure plans (APPCB, 2026).

The Andhra Pradesh District Mineral Foundation Rules also provide a mechanism for addressing environmental and community impacts in mining-affected areas. Leaseholders of major and minor minerals contribute to DMF funds, which may be used for water supply, mine drainage, pollution prevention, environmental restoration, and community infrastructure (Government of Andhra Pradesh DMF).

The Andhra Pradesh New Sand Policy, 2024 should not be cited as a controlling policy for the Phirangipuram granite quarry because it specifically addresses sand extraction. The relevant state framework consists of the minor-mineral concession rules, approved mining and closure plans, environmental-clearance conditions, APPCB requirements, and DMF provisions.

Overall, the 2023–2026 policy direction moves beyond simple end-of-lease plantation toward progressive reclamation, financial responsibility, quantitative monitoring, biodiversity recovery, water conservation, and community participation. The proposed Phirangipuram framework aligns with this direction by combining GIS-based terrain analysis, soil reconstruction, drainage restoration, native vegetation, assisted natural regeneration, field validation, and long-term monitoring.

III. Quarry Disturbance Processes

A. Operational sequence and disturbance pathways

Granite extraction typically progresses from site clearance and overburden removal to drilling, blasting or cutting, loading, haulage, processing, and waste placement. Environmental effects accumulate across these stages. Vegetation clearance removes habitat and exposes soil; overburden stripping eliminates the most biologically active growth medium; blasting creates fractured faces and vibration; traffic produces dust and compaction; and uncontrolled waste placement modifies surface runoff. Closure planning is most effective when topsoil conservation, drainage, progressive bench treatment, and final landform design begin during operation rather than after extraction ends (Hartman and Mutmansky, 2002).

Flow Diagram 2: GENERALIZED SEQUENCE OF MINING AND QUARRYING ACTIVITIES AND THEIR PRINCIPAL DISTURBANCE PATHWAYS.




TABLE I. QUARRY PHASES, DISTURBANCES, AND CORRESPONDING RECLAMATION CONSIDERATIONS.

Phase	Primary Disturbance	Reclamation Implication
Site preparation	Vegetation removal and topsoil stripping	Survey baseline conditions; salvage and separately store viable topsoil.
Extraction	Benches, pit walls, vibration, exposed rock	Design final slopes progressively; map discontinuities and unstable blocks.
Material handling	Dust, traffic, compaction, spills	Control dust and runoff; designate service and spill-response areas.
Waste placement	Dump instability, erosion, drainage obstruction	Engineer dump geometry; segregate potentially useful growth media.
Closure	Residual hazards and abandoned infrastructure	Remove hazards; establish drainage, vegetation, access control, and monitoring.

B. Interacting landscape elements

Landform, soil, vegetation, and water should be assessed as an integrated system. Benches and pit walls control runoff and access; loose soil and waste deposits determine erosion potential; vegetation influences surface protection and habitat; and pit geometry controls water storage and overflow. Changes to any one component affect the others. For example, placing soil on an excessively steep face is unlikely to succeed, while planting below an uncontrolled drainage outlet may expose young vegetation to scour. Figure 1 identifies common quarry elements that should be mapped before reclamation design.

Fig. 1. landscape elements in an open quarry, including pit crest, benches, haul roads, waste deposits, exposed rock, loose soil, vegetation, and water accumulation.



TABLE II. PRINCIPAL ENVIRONMENTAL EFFECTS AND RESPONSE PRIORITIES.

Environmental component	Typical impact	Priority response
Landform	Pits, benches, steep faces, unstable dumps	Geotechnical assessment, grading, scaling, access.
Soil	Topsoil loss, compaction, low organic matter, salinity or alkalinity	Characterization, amendment, erosion control, reconstructed growth medium.
Water	Drainage interruption, sediment, ponding, possible hydrocarbons	Source control, clean/dirty water separation, sediment treatment, water-quality testing.
Vegetation and habitat	Clearance, fragmentation, invasive colonization	Protect remnants; use staged native revegetation and habitat connectivity.
Community and landscape	Dust, noise, visual exposure, loss of productive land	Buffering, safe access, compatible reuse, stakeholder participation.

IV. CASE-STUDY EVIDENCE AND INTERPRETATION

The study was conducted using a representative granite quarry located near Phirangipuram, Guntur District, Andhra Pradesh, India, selected due to its typical hard-rock quarry characteristics and the presence of significant post-mining environmental disturbances. The site provides a suitable case for examining the ecological and physical impacts of granite extraction and evaluating sustainable reclamation strategies applicable to abandoned and inactive quarry landscapes.

The case study integrated multiple sources of evidence, including Geographic Information System (GIS) datasets, field observations, photographic documentation, topographic maps, and environmental resource maps developed during the original landscape planning investigation. Spatial datasets comprised land-use and land-cover maps, digital elevation models (DEM), slope and relief analyses, soil classification, drainage networks, groundwater distribution, flood susceptibility, and vegetation indices. These datasets were analyzed collectively to understand the interactions among terrain characteristics, hydrological processes, vegetation patterns, and anthropogenic disturbances resulting from quarrying activities.

Field investigations were undertaken to verify spatial observations and document site-specific environmental conditions, including quarry benches, exposed rock surfaces, waste rock dumps, remnant vegetation, erosion features, surface water accumulation, access roads, and disturbed landforms. These observations provided essential qualitative evidence for validating GIS interpretations and identifying environmental constraints that could not be fully captured through spatial datasets alone.

The interpretation of the case study followed a systematic environmental assessment framework consisting of five analytical stages:

- Landform Assessment – Evaluation of quarry morphology, slope gradients, relief characteristics, and geotechnical stability to identify areas requiring stabilization and safe landform reconstruction.
- Hydrological Assessment – Analysis of natural drainage patterns, runoff pathways, groundwater conditions, seasonal water accumulation, and flood-prone areas to determine suitable water management and erosion control measures.
- Soil and Vegetation Assessment – Examination of soil conditions, vegetation distribution, natural regeneration potential, and degraded surfaces requiring ecological restoration and soil rehabilitation.
- Environmental Risk Assessment – Identification of environmental hazards, including unstable quarry faces, erosion-prone slopes, sediment transport, habitat fragmentation, and potential impacts on adjacent agricultural land and surrounding ecosystems.
- Reclamation Suitability Assessment – Integration of spatial and field-based information to delineate restoration zones and recommend appropriate engineering, ecological, and landscape interventions based on site capability and long-term sustainability.

The spatial analyses were interpreted using GIS as a decision-support tool rather than as standalone predictive models. Consequently, the generated maps served to identify restoration priorities, environmental constraints, and opportunities for adaptive land use rather than to produce definitive engineering designs. Site-specific implementation would require supplementary geotechnical investigations, hydrogeological studies, soil testing, ecological inventories, and detailed engineering assessments before reclamation measures could be executed.

The integration of GIS-based spatial analysis with field observations enabled a comprehensive understanding of the environmental processes influencing quarry degradation and recovery. This approach facilitated the development of a scientifically informed reclamation framework that combines engineering stabilization, ecological restoration, sustainable water management, and landscape planning to support long-term environmental resilience and productive post-mining land use.

A. Case-Study Evidence 1: Restoration of Timba Basalt Quarry, Gujarat

Timba Quarry is a significant Indian example of restoring a degraded hard-rock quarry through assisted natural regeneration.

Located approximately 110 km southeast of Ahmedabad in the Pavagadh basalt, the 41-ha site contained excavations 15–20 m deep (Rao, 2014).

Between 1977 and 1985, Prabhakar B. Bhagwat and Associates replaced a proposed eucalyptus and Leucaena leucocephala monoculture with an ecological strategy based on soil, hydrology, topography and native vegetation. Topsoil and organic matter were spread over exposed basalt, followed by grasses, ground covers, shrubs and trees. Existing contours retained runoff and helped create a quarry water body. Human intervention was gradually reduced to allow natural succession.

Within approximately eight years, the quarry developed into a largely self-sustaining woodland and wetland ecosystem supporting diverse wildlife, including around 140 bird species annually. Timba demonstrates the importance of restoring soil and hydrological processes and establishing pioneer vegetation. However, differences in geology, climate and native species require locally adapted measures at Phirangipuram. Limited quantitative monitoring also means that Timba should be treated as a restoration precedent rather than definitive experimental evidence.

Landscape Architect: Prof. Prabhakar B. Bhagwat
Firm: Prabhakar B. Bhagwat & Associates, Ahmedabad
Restoration Period: 1977–1985

B. Case-Study Evidence 2: Wetland Restoration of Black Rock Sanctuary, Pennsylvania

Black Rock Sanctuary demonstrates the transformation of a degraded industrial site into a wetland habitat and environmental education park. Located in Phoenixville, Pennsylvania, the 120-acre former coal-silt basin was restored by KMS Design Group and completed in 2010.

Following environmental testing, more than 12,000 cubic yards of coal silt were removed and recycled. Grading created deepwater wetlands, shallow pools, nesting islands and vernal pools. The project created 27 acres of wetlands, improved another 19 acres and established native meadows, biofiltration cells, vegetated swales and a rain garden. Invasive species were replaced with native plants, and a 0.8-mile accessible interpretive trail supported recreation and education.

Recorded bird species increased from 63 in 2004 to 100 in 2011, while annual visitation rose from approximately 10,000 to 34,414 visitors. Relevant strategies for Phirangipuram include environmental testing, wetland creation, vegetated runoff treatment, invasive species control and interpretive trails. However, these measures must be adapted to Phirangipuram's granite geology, seasonal water availability and drier climate.

Landscape Architect: KMS Design Group, LLC
Completion: 2010

C. Case-Study Evidence 3: Restoration of Ramco's Old Limestone Quarries, Tamil Nadu

Ramco's Pandalgudi project is a recent Indian example of converting exhausted limestone quarries into native forest, wildlife habitat and a recreational eco-park. Located in Virudhunagar District, Tamil Nadu, the project was developed by Ramco Cements in collaboration with Auroville Botanical Gardens.

Restoration began in November 2018 with the removal of invasive Prosopis juliflora, reshaping of waste-rock piles and protection of existing ponds, rock formations and mature trees. Pioneer and native species were planted using Miyawaki and conventional restoration methods. The project also introduced ponds, streams, pathways, cycle tracks and an environmental-education centre.

By mid-2021, more than 220,000 trees and shrubs representing approximately 140 native varieties had been planted. The project expanded from about 65 acres to approximately 350–400 acres by 2023–2024. Relevant strategies for Phirangipuram include invasive-species removal, waste-rock stabilization, water-body conservation and phased native planting. However, differences between limestone and granite, along with the project's intensive planting and corporate funding, limit direct comparison. Because available information is primarily supplied by the project organizations, it should be treated as a documented precedent rather than independently verified evidence.

Client: Ramco Cements Limited
Restoration Consultant: Auroville Botanical Gardens
Restoration Commencement: November 2018
Eco-Park Inauguration: March 2022

D. Case-Study Evidence 4: Artistic Transformation of Butchart Gardens, Canada

Butchart Gardens illustrates the artistic and horticultural reuse of an abandoned limestone quarry. Located at Tod Inlet on Vancouver Island, the quarry formerly supplied limestone to Robert Butchart's cement plant.

Beginning in the early twentieth century, Jennie Butchart introduced topsoil across the quarry floor and benches while retaining the quarry walls, central limestone mound and level changes as landscape features. The 5-acre Sunken Garden was developed with winding paths, viewpoints, flower beds, trees and water features. The larger property later incorporated Japanese, Italian and Rose gardens as distinct outdoor spaces.

The 55-acre property was designated a National Historic Site of Canada in 2004. Its transferable strategies include retaining quarry walls, using elevation changes for viewpoints and organizing visitor movement through sequential spaces. However, its ornamental planting, intensive maintenance and humid climate limit direct application. At Phirangipuram, artistic reuse should instead be combined with native vegetation, water conservation and ecological succession.

Creator: Jennie Butchart
Japanese Garden Designer: Isaburo Kishida
Development Period: 1904–1939
Historic Designation: National Historic Site of Canada, 2004

TABLE III. PRINCIPAL ENVIRONMENTAL EFFECTS AND RESPONSE PRIORITIES. COMPARATIVE ANALYSIS OF CASE STUDIES

Comparative Quarry Reclamation Case Studies

Transcribed from the supplied image and lightly proofread for spelling, capitalization, and readability. Substantive values were preserved.

Name	Duration	Area	Location	Vegetation	Issues Before Redevelopment	Site Advantages	Method Used For Reclamation	Amenities Provided	Benefits
Basalt Quarry	8 years	41 ha / 15–20 m	Timba, Gujarat	Tropical dry deciduous woodland	Poor vegetation growth and disturbance of the natural ecological environment.	Contours and a quarry pit near a river.	Natural succession and development of a self-sustaining ecosystem.	Native planting and water diversion.	A natural environment supporting flora and fauna.
Black Rock Sanctuary	55 years	120 acres (48.6 ha) Not reported	United States	Temperate wetland and native meadow	Coal mining caused soil contamination, toxins and heavy metals, biodiversity loss, and river pollution.	Close to a river.	Restoration by filling the site with silt formed in the Schuylkill River and removing toxic materials from the silt.	Wetland trails, birdwatching decks, rain gardens, and butterfly gardens	Improved ecology and supported bird-watching and tourism development.
Ramco' s Old Limestone Quarries	Under process	Initially 65 acres to 350–400 acres / Not reported	Tamil Nadu	Tropical dry evergreen and thorn-scrub vegetation	Limestone quarries containing rocks, rubble, and thorny species.	Natural ponds within deep quarry areas.	A combined nature-and human oriented approach through development of a recreational forest.	Site grading, paths, ponds, tree planting, and interpretation	A recreational place for local communities.
Butchart Gardens	18 years	55 acres Not reported	Brentwood Bay, British Columbia, Canada	Temperate ornamental garden vegetation	An exhausted limestone quarry.	Close to a river.	Jennie Butchart planned an artistic transformation to create beauty within the large exhausted pit.	Themed gardens, seasonal events, recreation, dining, tours, and educational activities	Ecological development, educational opportunities, and cultural entertainment .

V. Integrated Reclamation Strategies

A. Landform and slope stabilisation

Slope safety is the first condition for ecological restoration and public reuse. Quarry slopes may consist of intact rock faces, jointed benches, loose colluvium, or unconsolidated waste; each requires a different treatment. Scaling, trim blasting, rock bolts, dowels, mesh, buttresses, drainage, and retaining structures can reduce immediate hazards. Bioengineering measures—live staking, brush layering, coir systems, erosion-control blankets, and deep-rooted vegetation—are more appropriate where a stable soil mantle can be established. Engineering and ecological measures are complementary: structural interventions address acute instability, while vegetation and surface-water control improve long-term resistance to erosion (Gray and Sotir, 1996; Wang et al., 2018).

Uniform slope angles should not be prescribed without geotechnical evidence. Gentle regraded slopes support soil retention and maintenance, but competent rock faces may be retained when setbacks, rockfall controls, and access restrictions are provided. Final landforms should also avoid long, planar surfaces that concentrate runoff and appear artificial. Benches, concave transitions, varied contours, and stable drainage outlets help integrate the quarry with surrounding terrain.

TABLE IV. Comparison of slope-stabilization approaches.

Method	Best application	Key limitation
Scaling/trim blasting	Loose blocks and hazardous overhangs	Requires specialist design; may create additional debris.
Rock bolts, dowels, mesh	Jointed rock requiring reinforcement or rockfall control	Cost, access, corrosion protection, and visual effects.
Regrading and buttressing	Loose material, waste dumps, accessible slopes	Large material movement and land take.
Surface/subsurface drainage	Water-driven erosion or instability	Requires maintained outlets and erosion protection.
Bioengineering and revegetation	Stable soil-covered slopes and drainage lines	Slow establishment; unsuitable as sole treatment for structural instability.

B. Soil rehabilitation and growth-media design

Revegetation success depends on the physical and chemical quality of the rooting medium. Salvaged topsoil is valuable because it contains organic matter, microorganisms, propagules, and locally adapted seed, but long stockpiling can reduce these qualities. Where topsoil is absent, a reconstructed growth medium can combine suitable overburden, fine quarry material, compost, mulch, or other tested amendments. Material must be assessed for texture, compaction, pH, salinity, nutrient availability, metal content, and water-holding capacity before placement (Tordoff et al., 2000; Lottermoser, 2010, Talento, K., 2025).

Alkaline or sodic conditions may require gypsum or other amendments, while saline areas depend primarily on drainage and salt management (Rengasamy, 2006). Amendment rates should never be transferred directly from a generic guideline to a site without laboratory testing. Deep ripping, roughening, contour placement, mulch, and temporary erosion controls improve infiltration and reduce early soil loss. The objective is not merely to achieve short-term green cover but to establish a stable soil–plant system capable of succession.

Monitoring should measure survival, ground cover, erosion, invasive species, soil condition, and habitat development rather than relying only on the number of plants installed. Failed areas require diagnosis before replanting. Persistent failure may indicate unstable substrate, inadequate drainage, unsuitable species, grazing, or insufficient maintenance rather than a simple shortage of plants. Field studies of quarry revegetation similarly show that stabilized growth media and site-appropriate establishment methods are prerequisites for durable cover (Zhang et al., 2017).

Fig. 2. Vegetation conditions observed in disturbed quarry environments: remnant trees, spontaneous pioneer growth, vegetation in rock fissures, moisture associated colonization, and contrasting vegetation patches. Source: field documentation.




C. Water management

Quarry pits can intercept runoff and, in some settings, groundwater. Water may become an asset for storage, habitat, irrigation support, or recreation, but only after quantity, quality, seasonal behavior, and overflow risk are understood. Clean runoff should be separated from water exposed to disturbed material or service areas. Sediment controls, energy dissipation, stable spillways, and monitoring points should be integrated into the final landform because extraction-related channel disturbance can alter erosion and sediment transport (Kondolf, 1997). Hydrocarbon contamination from equipment washing or maintenance requires source control and remediation rather than dilution (Younger et al., 2002).

The Guntur material indicates marked seasonal groundwater conditions and dependence on monsoon rainfall and irrigation canals. These patterns strengthen the case for designing reclamation around seasonal water movement rather than treating drainage as a secondary detail.

Fig. 3. Groundwater and rainfall evidence used in the original assessment, including pre-monsoon and post-monsoon conditions. Source: Guntur Municipal Corporation map



D. Adaptive reuse

Post-mining use should follow, not precede, an assessment of residual risk and landscape capacity. Potential outcomes include ecological reserves, woodland, agriculture or agroforestry, water storage, research or education sites, trails, viewpoints, parks, and carefully controlled development. Deep pits and unstable walls may favor restricted ecological or water-management uses, whereas accessible, stable benches near settlements may support public programs. International examples demonstrate that

quarry landscapes can become valuable community assets, but iconic adaptive reuse should not obscure the importance of long-term safety, water management, access, and operating finance (Wang et al., 2018).

VI. Guntur–Phirangipuram Case Study

A. Guntur setting

The case-study landscape lies within the Guntur, Andhra Pradesh, where agriculture, settlements, irrigation infrastructure, and granite extraction coexist. The broader terrain contains productive agricultural soils and monsoon-dependent vegetation, but quarry activity has introduced exposed rock, waste deposits, altered contours, and localized drainage interruption. Diagnosis is important because reclamation performance depends on off-site water movement, seed sources, land-use compatibility, access, and community practices as much as on conditions inside the lease boundary.

Fig. 4. Gunture planning evidence: land-use context, soil distribution, vegetation pattern, and topographic setting in the Guntur. Source: Guntur Municipal Corporation map






Fig. 5. Interpreted 1980–2023 landscape-change sequence showing vegetation clearance, quarry expansion, access development, waste accumulation, and pit water formation. Source: author's Google satellite image



The presentation reconstructs a 2000–2020 sequence in which the site changed from a vegetated hill or agricultural-edge landscape to an increasingly cleared and excavated quarry with service access, expanding disturbed surfaces, waste accumulation, and pit-water formation. The timeline is valuable because it demonstrates that degradation was progressive rather than instantaneous. This supports progressive reclamation: areas no longer required for extraction should be stabilized during operations, not deferred until final closure.

Fig. 6. Visitors, Site survey conducted on site with the help of local peoples



B. Geospatial Data Source and Analysis

Digital geospatial datasets were obtained from the Bhuvan Open EO Data Archive, maintained by the National Remote Sensing Centre (NRSC), Indian Space Research Organisation (ISRO), Government of India, Hyderabad. The study area is centred near Phirangipuram, Guntur District, Andhra Pradesh, at approximately 80.41916° E and 16.39533° N.

Terrain analysis was conducted using the CartoDEM 1-arc-second digital elevation model, with an approximate spatial resolution of 30 m. Vegetation and surface-water conditions were examined using a Resourcesat-1 LISS-III scene acquired on 19 November 2011. The LISS-III sensor provides multispectral data at approximately 23.3 m spatial resolution. Red (Band 3) and near-infrared (Band 4) bands were used to calculate the Normalized Difference Vegetation Index (NDVI), while green (Band 2) and shortwave infrared (Band 5) bands were used to calculate the Modified Normalized Difference Water Index (MNDWI).

Terrain analysis was conducted using the CartoDEM 1-arc-second digital elevation model, with an approximate spatial resolution of 30 m. Vegetation and surface-water conditions were examined using a Resourcesat-1 LISS-III scene acquired on 19 November 2011. The LISS-III sensor provides multispectral data at approximately 23.3 m spatial resolution. Red (Band 3) and near-infrared (Band 4) bands were used to calculate the Normalized Difference Vegetation Index (NDVI), while green (Band 2) and shortwave infrared (Band 5) bands were used to calculate the Modified Normalized Difference Water Index (MNDWI).

The source datasets were supplied in the WGS 84 geographic coordinate system (EPSG:4326). Before calculating distances, areas, slopes, contours, and hydrological characteristics, all datasets were projected to WGS 84/UTM Zone 44N (EPSG:32644). GIS processing was completed using [software name and version, such as QGIS 3]. Raster layers were clipped to the study boundary and aligned to a common spatial extent. The original pixel resolution of each dataset was retained wherever possible. Where raster alignment was required, bilinear interpolation was used for continuous data, such as elevation and spectral indices, while nearest neighbour resampling was used for categorical LULC data.

The CartoDEM 30 m dataset was selected because it is an authoritative, freely accessible, nationally standardised elevation product suitable for regional-scale terrain, drainage, slope, and watershed analysis in India. Its resolution is sufficient for identifying general landform patterns, drainage directions, catchment relationships, and broad slope constraints relevant to strategic quarry reclamation planning.

However, the 30 m DEM cannot reliably represent individual quarry benches, steep quarry faces, small drainage channels, or detailed pit geometry. Therefore, DEM-derived elevations and drainage patterns were interpreted at the landscape-planning scale and verified using a GPS Waypoints android mobile app survey.

TABLE V. RECOMMENDED SATELLITE DATA

Required map	Recommended satellite/data	Files or bands required	Spatial Resolution
Contour map	CartoDem-1 arc Sec / CartoDEM Version	Digital elevation model in GeoTIFF format	Approximately 30 m
Streams/drainage	CartoDem-1 arc Sec / CartoDEM Version	DEM used for flow direction and accumulation	30 m
Vegetation/NDVI	Resourcesat LISS-III	Band 3—Red and Band 4—Near Infrared	23.3 m
Water bodies	Resourcesat LISS-III	Band 2—Green and Band 5—SWIR	23.3 m
Land-use map	Bhuvan SIS-DP Phase 2 LULC	NRSC thematic land-use dataset	1:10,000 mapping scale; source imagery approximately 5.8 m

The inspected Resourcesat-1 LISS-III scene was acquired on 19 November 2011. The Bhuvan SIS-DP Phase 2 LULC dataset represents the 2018–2023 national mapping cycle. The specific acquisition date and publication period of each dataset were recorded separately to avoid presenting the datasets as belonging to a single observation period.

C.1 Contour Generation

QGIS version 3.14 was used for raster preparation, visualization, and contour generation. Contours were generated from the projected CartoDEM using a 10 m contour interval. Contour elevations were calculated as

[C_n=B+(nI)]

where (C_n) is the contour elevation, (B) is the base contour, (I) is the contour interval, and (n) is an integer. With a base contour
of 0 m and an interval of 10 m

[C_n=0+(n)]

This produced contours at 0, 10, 20, 30, 40, and 50 m, continuing throughout the elevation range. Because CartoDEM has an approximate spatial resolution of 30 m, the contours were used for terrain interpretation rather than detailed engineering or quarry bench design.

C.2 Stream and Drainage Delineation

Hydrological analysis was performed in ArcGIS Pro using the CartoDEM elevation raster. The DEM was hydrologically conditioned using the Fill tool, followed by D8 Flow Direction and Flow Accumulation analyses. The contributing drainage area was calculated as

[A=(FA+1)C_xC_y]

where (A) is the contributing drainage area, (FA) is the flow-accumulation value, and (C_x) and (C_y) are the raster-cell dimensions. For a 30 m DEM

[A=(FA+1)]

Cells exceeding the selected flow accumulation threshold were classified as potential drainage channels. The resulting stream network was converted into vector lines and compared with identifiable drainage features in the satellite imagery and Bhuvan thematic data.

GPS point system using the gps point finding the msl of the particular place using Waypoints

C.3 Vegetation Analysis

Vegetation distribution was evaluated using the Normalized Difference Vegetation Index (NDVI). NDVI was calculated from LISS-III Band 4, representing near infrared reflectance, and Band 3, representing red reflectance

[NDVI= B4-B3/B4+B3]

Higher positive values indicate comparatively denser or healthier vegetation, while values approaching zero or becoming negative generally represent exposed rock, barren land, built surfaces, or water. The resulting NDVI raster was classified into non vegetated, sparsely vegetated, moderately vegetated, and densely vegetated areas.

NDVI values below 0.00 represent water, shadows, or non-vegetated surfaces; values from 0.00 to 0.20 indicate bare rock, quarry surfaces, or built-up land; values above 0.20 to 0.40 represent sparse vegetation; values above 0.40 to 0.60 indicate moderate vegetation; and values above 0.60 represent dense vegetation.

C.4 Water Body Analysis

Surface water features were identified using the Modified Normalized Difference Water Index (MNDWI). The index was calculated using LISS-III Band 2, representing green reflectance, and Band 5, representing shortwave infrared reflectance:

[MNDWI= B2-B5/B2+B5]


Positive MNDWI values were initially treated as potential water features. The classification threshold was subsequently checked against visible water bodies and quarry shadows because shaded rock surfaces can produce spectral responses similar to water.

All spatial outputs were clipped to the study area, checked for coordinate consistency, and prepared with standardised legends, north arrows, scale bars, coordinate references, data source citations, and acquisition dates.

C.5 City and catchment-scale interpretation

The city scale maps indicate an agricultural and peri-urban matrix around the quarry landscape. Topographic and hydrological patterns suggest that disturbed contours can redirect runoff toward low areas and the quarry pit. Vegetation-index mapping distinguishes active vegetation from exposed or sparsely vegetated surfaces, while the flood layer identifies areas where temporary water storage and controlled diversion may reduce impacts on cropland. Because map dates and accuracy statistics are incomplete, these layers should guide field verification rather than serve as final design documentation.

Fig. 7. Topographic, Hydrology, Flood Map. Source : QGIS generated



C. Topography Map

The topographic analysis indicates that the highest elevation within the study area is approximately 171 m above mean sea level and corresponds to the granite quarry zone. The lowest elevation is approximately −34 m, primarily resulting from deep excavation associated with quarrying activities. The map uses a contour interval of 5 m, clearly illustrating the substantial elevation variation and altered terrain produced by mineral extraction.

D. Hydrology Map

The hydrological analysis shows that the terrain generally slopes toward the southeast, influencing the direction of surface-water runoff. Water originating from the Krishna River is conveyed through the Nagarjuna Sagar Right Canal and distributed for irrigation across the surrounding agricultural areas. The existing drainage pattern should be considered when developing quarry-reclamation and stormwater-management strategies.

E. Flood Map

Flash flooding is a significant environmental concern within the study area, particularly during February and March, which coincide with the cropping season. Inadequate drainage causes floodwater to accumulate in agricultural fields, resulting in crop damage and adverse economic impacts on local farmers. An integrated stormwater-management plan could redirect excess runoff into abandoned quarry pits for temporary storage. This strategy may reduce flooding in agricultural areas while supporting groundwater recharge and the ecological reclamation of the quarry.

2015; Filho et al., 2022) identified persistent limitations: vendor lock-in, inadequate participation, and failure to address climate resilience.

Fig. 8. City- and catchment-scale analysis: topography, normalized difference vegetation index, hydrology, and flood-related conditions. Source:. QGIS generated



F. Normalized Difference Vegetation Index (NDVI) Map


The Normalized Difference Vegetation Index (NDVI) is widely used to assess the distribution, density, and health of vegetation based on the reflectance characteristics of plants at different wavelengths. NDVI values range from −1 to +1. Negative values generally represent water bodies, while values close to zero (approximately −0.1 to +0.1) indicate barren surfaces such as exposed rock, sand, or quarry areas. Low positive values between approximately 0.2 and 0.4 represent grasslands and shrub vegetation, whereas higher values indicate dense and healthy vegetation.

The NDVI analysis shows that the study area is predominantly surrounded by agricultural land, with settlement areas concentrated along one side of the quarry. The exposed quarry surfaces exhibit low NDVI values due to the absence of vegetation. These spatial variations provide a baseline for identifying degraded areas and planning vegetation-based quarry reclamation.

VII. SITE-SCALE CONSTRAINTS AND OPPORTUNITIES

At the site scale, the quarry is characterized by a stepped excavation, exposed rock, localized steep faces, waste deposits, sparse spontaneous vegetation, and water accumulation in lower areas. The relief and slope maps identify zones where direct planting would be unreliable without stabilization or soil reconstruction. The site-level vegetation layer also shows that some disturbed surfaces retain ecological recovery potential. These patterns support a zoned strategy: restricted stabilization areas at hazardous faces, active soil and vegetation treatment on accessible slopes, water-management areas around the pit, and conservation of remnant vegetation wherever it does not conflict with safety.


Fig. 9. Site-scale spatial analysis: topography, relief, slope,. Source: QGIS generated



A. Contour Analysis

Before quarrying began, the site consisted of a hillock approximately 20 m high. Continuous extraction has substantially altered the original landform, creating a stepped open pit that reaches approximately 15 m below the surrounding ground level. Waste-rock dumps are also present but are proposed to be transported from the site. The depressed quarry floor collects surface runoff, resulting in permanent or seasonal waterlogging and the formation of a pond.

Fig. 10. Site section



B. Relief Map

The relief map demonstrates the substantial vertical transformation caused by quarrying. The site contains abrupt elevation differences between the quarry rim, stepped excavation levels, waste-rock deposits, and the pit floor. Certain excavated faces approach a 90° angle, creating potentially dangerous and unstable conditions. These areas require stabilization and controlled grading as part of the reclamation strategy.

C. Slope Analysis


The slope analysis indicates that most of the site is relatively flat, with gradients of less than 5%. However, the quarry edges and exposed rock faces contain extremely steep slopes, in approaching 90°. These steep faces present risks of rockfall, erosion, and slope failure. Appropriate measures—including benching, slope stabilization, drainage control, safety barriers, and vegetation establishment—are therefore required.

D. Hydrology Map

Quarrying has disturbed the natural contours and interrupted established surface-water flow paths in several parts of the site. Excavation has also created new drainage channels that direct runoff toward the quarry pit, contributing to water accumulation. Mechanical pumping and artificial diversion methods are currently used to manage this water. Future reclamation should restore drainage continuity and integrate the quarry pond into a sustainable stormwater-management system.

The open pit covers approximately 1 ha (10,000 m^2) and has an average depth of 10 m, providing a theoretical storage capacity of approximately 100,000 m^3. Based on an average seasonal rainfall of 18.5 cm (0.185 m), direct rainfall over the pit would contribute approximately 1,850 m^3 of water per season. This represents approximately 1.85% of the pit's theoretical capacity. The actual stored volume would be lower because of evaporation, infiltration, seepage and overflow losses. Additional recharge may occur through surface runoff from the surrounding catchment; however, this contribution requires catchment delineation and site-specific runoff coefficients. Therefore, the pit should be considered a potential seasonal water-storage feature rather than a confirmed permanent water source.

Fig. 11. Site-scale spatial analysis: topography, relief, slope,. Source QGIS generated



E. Normalized Difference Vegetation Index (NDVI)

The Normalized Difference Vegetation Index (NDVI) is an effective method for evaluating vegetation distribution, density, and health based on the spectral reflectance characteristics of plants. NDVI values range from −1 to +1. Negative values generally represent water bodies, while values close to zero (approximately −0.1 to +0.1) indicate barren surfaces such as exposed rock, sand, and quarry areas. Low positive values between approximately 0.2 and 0.4 represent grasslands and shrubs, whereas higher values indicate dense and healthy vegetation.

The NDVI analysis shows that the quarry contains extensive exposed and sparsely vegetated surfaces. The surrounding landscape is predominantly agricultural, while settlement areas are concentrated along one side of the site. This spatial pattern provides a baseline for identifying degraded zones and selecting priority areas for vegetation-based reclamation.

F. Plant Species Identified on the Site

Field observations identified the following tree and palm species within and around the quarry site: Acacia nilotica , Azadirachta indica , Tamarindus indica , Ficus religiosa , Phoenix sylvestris , Borassus flabellifer

These locally established species demonstrate their adaptability to the site's climatic and soil conditions and may inform species selection for ecological restoration.

G. Crops Identified

The agricultural areas surrounding the quarry primarily contain the following crops and cultivated species : Guava (Psidium guajava) , Cotton (Gossypium spp.) , Rice (Oryza sativa)

The presence of these crops highlights the importance of controlling quarry runoff, sediment movement, dust, and flooding to protect surrounding agricultural productivity.

Fig. 12. Selected field conditions at the quarry: exposed and fractured rock, waste piles, remnant vegetation, access routes, and disturbed surfaces. Source: field photographs.



TABLE VI. CASE -STUDY DIAGNOSIS AND RECOMMENDED RESPONSE .

Observed condition	Risk or limitation	Reclamation Response
Steep and fractured quarry faces	Rockfall and limited planting access	Geotechnical mapping, scaling or reinforcement, setbacks, restricted access.
Waste rock and scattered debris	Instability, poor visual quality, blocked drainage	Characterise and reuse suitable material; remove debris; regrade stable landforms.
Sparse soil and exposed rock	Low water retention and limited rooting depth	Create planting pockets or reconstructed growth media only on stable surfaces.
Remnant native vegetation	Potential damage during earthworks	Survey, protect, and use as seed and habitat reference.
Pit-water accumulation	Water-quality and overflow uncertainty	Seasonal water balance, quality testing, stable spillway, and defined end use.
Agricultural surroundings	Dust, runoff, and land-use conflict	Buffers, clean-water diversion, stakeholder consultation, compatible reuse.

TABLE VII. DIGITAL DATA ANALYSIS

quarry recovery typologies		quarry type		excavation metho		pit/side sizes		quarrry depth		rain fall		proximity of	land use			landscape results
		mountain	plain	stepped	plate	small	large	samall	large	low	average /good		urban	rural	far away form settlements	
filling	water															lakes leasure space fishing
	soil															parks play grounds treacks
	muncipal waste															parks muncapal treatment plants
	buildings															housing
slopes modification	quarry slopes															plantation view points trails
	vaste dump slopes															plantation view points trails
functional zones	view points															with safty and proper monutering
	trails															
	core activities															
	functional purpuse authorities use															
vegetation																
buffer	hazards places															
	green belt															
	noise and sound															
	visual															few view are spefied

VIII. Proposed Reclamation Framework for Eco tourism

The evidence supports a five-phase framework in which each phase establishes the conditions required by the next. The sequence is iterative: monitoring can trigger renewed stabilization, soil treatment, or planting. The framework is intentionally performance-based so that treatments can be adapted to geology, climate, regulation, land ownership, and community priorities.

Flow Diagram 3: GENERALIZED SEQUENCE OF MINING AND QUARRYING ACTIVITIES AND THEIR PRINCIPAL DISTURBANCE PATHWAYS.





TABLE VIII. PHASED RECLAMATION AND PERFORMANCE FRAMEWORK.

Phased Quarry-Reclamation Action Matrix									
Regional-Level Measures									
Water Connections		**Site Boundary**	**Visual, Noise and Pollution**			**Community Motivation**			
Reconstruct disconnected drainage channels.		*Install Boundary.*	*Use phased planting to reduce visual, noise and pollution impacts.*			Educate the Public.	Involve local communities.	Support tourism development.	
		safety measures and signage.							
Divert water toward the site. Maintain waterlogged areas and drainage channels.		*Establish visual and planting.*	*Implement beautification and functional landscape measures. noise-buffer*			Coordinate through local students.	Engage farmers and leaders.	Promote the site to regular visitors.	
			Site-Level Measures						
Engineering Measures						Vegetative Measures		Tourism	
Stabilize artificial slopes; install barriers, gates and signage.	Divert water; construct channels and install geomembranes where required.	Implement site-safety measures.	Construct retaining walls where necessary.	Apply traditional mixed-cropping methods.	Plant shade-tolerant species around existing vegetation.	Retain compatible pioneer activities, weeds and ground cover.	Provide planting student involvement and walking trails.	Divert water; construct channels and install geomembranes where required.	
Manage visitor inflow						Vegetative measures			
Provide play equipment and visitor facilities.	Create spaces for different activities.	Shape exposed rock for safe use and interpretation.	Establish a plant nursery. surfaces	Increase tree cover.	Introduce locally suitable species that support wildlife habitat.	Use Allow productive natural species that succession can benefit with minimal local disturbance. communities.		Provide play equipment and visitor facilities.	

The abandoned granite quarry into a multifunctional landscape organized around four components: vegetation, safety, activities, and art. Ecological restoration includes native planting, peripheral vegetation buffers, wetland vegetation, agroforestry, and an onsite nursery supported by local participation. Safety measures include slope stabilization, hazard-zone identification, protective barriers, signage, road-safety improvements, and buffers around utility infrastructure. Low-impact visitor activities include walking trails, bird-watching decks, picnic and educational areas, controlled rock climbing, rope walks, nature camping, and community planting programs. Quarry waste rock and reusable metal materials are proposed for landscape art, interpretive installations, seating, and culturally oriented event spaces. Together, these interventions support biodiversity recovery, environmental education, community involvement, and local economic opportunities while retaining the quarry's geological and cultural identity.

Fig. 13. Selected field conditions at the quarry: exposed and fractured rock, waste piles, remnant vegetation, access routes, and disturbed surfaces. Source: field photographs.



IX. Discussion

A. From Visual Repair to Landscape Performance

A central finding of this study is that quarry reclamation should be evaluated through environmental and social performance rather than visual appearance alone. Vegetation may visually soften a disturbed site while leaving unstable slopes, contaminated water, erosion, or failing drainage unresolved. Conversely, a stabilized rock face or functioning stormwater basin may initially appear less "green" but provide an essential foundation for long-term ecological recovery and safe public use. Reclamation performance should therefore be evaluated using transferable criteria, including slope stability, erosion and sediment control, water quality, soil function, vegetation establishment, habitat connectivity, visitor safety, community benefit, and long-term stewardship.

For an ecotourism-oriented quarry, visual improvement should be treated as one outcome of environmental recovery rather than its primary objective. Trails, viewing platforms, climbing areas, camping facilities, and cultural spaces should be introduced only after geotechnical hazards, drainage problems, and ecological sensitivities have been adequately addressed.

B. Progressive Reclamation and Circular Use of Materials

Progressive reclamation reduces the area remaining untreated at closure and enables operators to evaluate and refine restoration methods while equipment, materials, and technical expertise remain available. Topsoil, suitable overburden, stone fines, and waste rock may serve as reclamation resources when properly characterized, segregated, stored, and placed.

This circular approach can reduce material-import requirements, transportation impacts, and waste-disposal volumes. Waste rock may also be used for drainage structures, slope stabilization, trails, seating, landscape art, and interpretive features. However, reuse must be governed by geotechnical, hydrological, and environmental suitability. Materials should not be incorporated into the reclaimed landscape solely because they are locally available. Their physical stability, drainage behavior, potential contamination, and compatibility with vegetation establishment must first be evaluated.

C. Governance and Community Participation

A technically credible reclamation plan may still fail if land ownership, maintenance responsibility, funding, regulatory approval, and community expectations remain unresolved. Nearby residents and land users can identify seasonal flooding, informal access routes, valued views, grazing practices, cultural uses, and livelihood opportunities that may not be apparent through desktop or GIS analysis.

Community participation should therefore occur during baseline assessment, end-use selection, spatial zoning, implementation, and monitoring rather than only after the design concept has been completed. In the Guntur context, agricultural compatibility, water availability, dust control, local planting knowledge, visitor management, and opportunities for community-based tourism are particularly relevant.

Local participation could include nursery operations, planting and maintenance programs, environmental education, guided quarry tours, food and craft services, and management of low-impact visitor facilities. However, these opportunities require a clearly defined governance structure to ensure that tourism revenue contributes to ecological maintenance and community benefit.

D. Advancement Beyond Existing Quarry-Reclamation Models

Existing quarry-reclamation models commonly emphasize individual interventions, including natural succession, mine-waste revegetation, slope stabilization, soil improvement, water remediation, and site-specific adaptive reuse (Bradshaw, 1997; Tordoff et al., 2000; Wang et al., 2018; Navarro-Ramos et al., 2022; Talento, 2025). Although these approaches provide important ecological and technical guidance, they are frequently presented as separate treatments rather than as a coordinated implementation process for hard-rock quarry landscapes.

Traditional reclamation approaches also commonly treat stabilization, soil replacement, drainage control, and revegetation as final closure measures. Such approaches may provide limited guidance concerning spatial prioritization, community participation, longterm management, and selection of an environmentally appropriate post-quarry use.

The proposed framework advances beyond this fragmented treatment by integrating literature-derived evidence, field observations, multi-scale GIS diagnosis, geotechnical risk control, landform and drainage repair, soil and habitat reconstruction, staged native revegetation, spatial-priority zoning, community participation, ecotourism reuse, and long-term monitoring within a single phased structure. It recognizes that reclamation activities are interdependent: slope and drainage stabilization must support soil reconstruction; soil conditions must support vegetation establishment; and ecological recovery and safety conditions must determine the location and intensity of future visitor activities.

The framework also distinguishes ecological-restoration zones, safety and restricted zones, and controlled ecotourism and interpretation zones. This prevents recreation from being introduced uniformly across environmentally sensitive or physically hazardous areas. Monitoring results can trigger corrective stabilization, drainage modification, soil treatment, replanting, habitat protection, or visitor-control measures rather than allowing reclamation to remain a fixed end-of-mining plan.

The framework adapts internationally transferable reclamation principles to the climatic, agricultural, regulatory, and community conditions of Indian granite quarries. Its principal contribution is therefore not a new individual reclamation technique or a

construction-ready tourism design, but an integrated, spatially explicit, and performance-based planning framework that converts separate interventions into an adaptable sequence for progressive closure and long-term landscape recovery.

7.5 Limitations

This study has several limitations. First, the literature synthesis was structured but not fully systematic and may therefore omit relevant publications. Second, the case study was developed from an earlier landscape-architecture investigation rather than a new, statistically designed field campaign. Field observations and available site photographs supported interpretation, but contemporaneous quantitative ground-truth sampling was not conducted.

8. Conclusions

Granite quarry reclamation should be approached as the reconstruction of a functioning landscape rather than as visual repair or revegetation alone. Unlike traditional approaches that often treat slope stabilization, drainage, soil treatment, and planting as separate closure measures, the proposed framework integrates these actions into a phased process of risk control, hydrological and soil recovery, ecological restoration, adaptive reuse, and performance monitoring.

The Guntur–Phirangipuram case demonstrates how steep quarry faces, exposed rock, altered drainage, limited growth media, waste deposits, pit-water accumulation, remnant vegetation, and surrounding agricultural land can be organized through spatial priority zoning. These zones identify areas for ecological restoration, water management, restricted access, and controlled public use. However, GIS findings must be verified through current geotechnical, hydrological, ecological, and field investigations before implementation.

Ecotourism provides a potential long-term reuse strategy after safety and ecological performance have been established. Low impact recreational trails, bird-watching decks, geological viewing areas, controlled climbing, nature camping, and restored wetland areas could support recreation without compromising sensitive habitats. Educational programs, interpretive signage, guided quarry tours, student planting activities, and demonstration nurseries could communicate the site's geological history and restoration process. Community reuse may include locally managed nurseries, cultural events, guided tourism, craft and food services, and maintenance employment, allowing restoration benefits to extend beyond the quarry boundary.

The study contributes an integrated strategic planning framework rather than a construction-ready design. Future research should test it through monitored pilot projects and evaluate ecological recovery, visitor carrying capacity, public safety, community participation, and socioeconomic benefits. Long-term monitoring should guide corrective stabilization, drainage improvement, replanting, habitat protection, and visitor management as site conditions change.

X. References

Ashmole, I., Motloung, M., 2008. Reclamation and environmental management in dimension stone mining. In: Surface Mining 2008. Southern African Institute of Mining and Metallurgy, Johannesburg, pp. 155–178.

Bradshaw, A.D., 1997. Restoration of mined lands—using natural processes. Ecological Engineering 8(4), 255–269. https://doi.org/10.1016/S0925-8574(97)00022-0.

Gray, D.H., Sotir, R.B., 1996. Biotechnical and Soil Bioengineering Slope Stabilization: A Practical Guide for Erosion Control. Wiley, New York.

Hartman, H.L., Mutmansky, J.M., 2002. Introductory Mining Engineering, second ed. Wiley, Hoboken.

Kondolf, G.M., 1997. Hungry water: Effects of dams and gravel mining on river channels. Environmental Management 21(4), 533–551. https://doi.org/10.1007/s002679900048.

Lottermoser, B.G., 2010. Mine Wastes: Characterization, Treatment and Environmental Impacts, third ed. Springer, Berlin.

Navarro-Ramos, S.E., et al., 2022. Active revegetation after mining: What is the contribution of peer-reviewed studies? Heliyon 8(3), e09179. https://doi.org/10.1016/j.heliyon.2022.e09179.

Rengasamy, P., 2006. World salinization with emphasis on Australia. Journal of Experimental Botany 57(5), 1017–1023. https://doi.org/10.1093/jxb/erj108.

Tordoff, G.M., Baker, A.J.M., Willis, A.J., 2000. Current approaches to the revegetation and reclamation of metalliferous mine wastes. Chemosphere 41(1–2), 219– 228. https://doi.org/10.1016/S0045-6535(99)00414-2.

Wang, H., Zhang, B., Bai, X., Shi, L., 2018. A novel environmental restoration method for an abandoned limestone quarry with a deep open pit and steep palisades: A case study. Royal Society Open Science 5, 180365. https://doi.org/10.1098/rsos.180365.

Worlanyo, A.S., Jiangfeng, L., 2021. Evaluating the environmental and economic impact of mining for post-mined land restoration and land-use: A review. Journal of Environmental Management 279, 111623. https://doi.org/10.1016/j.jenvman.2020.111623.

Younger, P.L., Banwart, S.A., Hedin, R.S., 2002. Mine Water: Hydrology, Pollution, Remediation. Kluwer Academic Publishers, Dordrecht.

Zhang, C., et al., 2017. Revegetation in abandoned quarries with landfill stabilized waste. Solid Earth 8, 1131–1142. https://doi.org/10.5194/se-8-1131-2017.

Ramco Cements Limited. (2021). Delivering Value Through Conscious Manufacturing: Sustainability Report. Ramco Cements Sustainability Report

Auroville Botanical Gardens. (2024). Pandalgudi Mine Eco-Restoration Project. Pandalgudi project

Auroville Botanical Gardens. (2023). Activities at the Gardens 2022–2023. Annual report
Hao, P., 2025. Integrating Ecological Restoration, Material Reuse, and Heritage Protection in Post-Industrial Quarry Landscape Regeneration. Landscape Architecture Frontiers 13(2), 82–85. https://doi.org/10.15302/J-LAF-1-040037
Talento, K., 2025. The Rehabilitation of Quarries. In: Sustainable Buildings from Marble Waste Heaps. Springer, Cham. https://doi.org/10.1007/978-3-031-72146-
5_3
Geoheritage (2024). Examples of Good Practices in the Reclamation and Use of Abandoned Quarries. Geoheritage 16, article (2024). https://doi.org/10.1007/s12371024-00934-0

Delight in Nature with Earth Walks Club!

Go Walk! Go Green! Earth Walkers!



Are you looking to escape the daily hustle and reconnect with the **natural world?** Earth Walks Club is your dedicated environmental **tourism consultant**, helping you discover breathtaking natural landscapes, serene retreats, and thrilling outdoor escapes.

What We Do:

Bespoke Nature Travel Consulting: We curate recommendations and highlight extraordinary destinations where you can immerse yourself in nature.

Environmental & Nature Tourism Focus: Whether it is a sun-drenched beach escape or a lush tropical trail, we guide you toward destinations that champion the beauty and preservation of the environment.

Important Note: We are independent travel consultants and focus purely on advisory and destination inspiration. We do not process bookings or handle tour reservations directly, giving you complete freedom to plan your trip your way.

Discover your next natural escape today!

EARTH WALKS

Connect with us: Earth Walks Club

EXPERT INTERVIEW

Professor Michael Mainelli

Professor Michael Mainelli

Part I: Hard Engineering, Space Infrastructure, & Green Finance

Question 1: Space Debris and Orbital Environmental Protections

Through Z/Yen's *Space Protection Initiative*, you have championed Space Debris Removal Insurance Bonds (SPADRIBs) to keep space "clutter-free". ***How can we translate this type of performance-bond model to terrestrial eco-tourism infrastructure to ensure that developers are financially accountable for the long-term decommissioning or recycling of their sites?***

Performance and surety bonds work because they convert a promise into a priced obligation. A SPADRIB - a Space Debris Removal Insurance Bond , isn't clever because it's about space; it's clever because it forces a launch operator to post capital against a future clean-up they'd rather forget about once the satellite is up and the champagne is drunk. The same logic transfers to eco-tourism sites with almost no translation required.

Think of a “DEDRIB” - a Decommissioning and Debris Removal Insurance Bond , for a rainforest lodge, a polar research-tourism base, or a deep-sea observation platform. The developer posts a bond at construction, sized actuarially against the cost of full site restoration (not partial, not “best efforts” - full). The bond sits with an independent trustee, accrues interest, and is released on verified decommissioning, inspected by a third party against a pre-agreed restoration standard. If the operator walks away, disappears, or goes

bankrupt , which happens more often in adventure tourism than anyone likes to admit , the bond pays for restoration regardless.

Core to the orbital version, and the bit I'd insist eco-tourism keeps, is that the bond premium is priced dynamically, not set once and forgotten. Debris risk in orbit changes as congestion changes; site risk in a fragile ecosystem changes as visitor numbers, storm frequency, or permafrost melt change. A static bond becomes a subsidy for negligence within a decade. A dynamically re-priced one keeps developers honest for the life of the asset, not just at ribbon-cutting.

In short, we move from the wasteful 'build–operate–abandon' paradigm to a disciplined 'build–operate–restore' lifecycle where capital markets enforce operational rigor. Eco-tourism should not merely minimise harm; it must guarantee total ecological reversibility.

Question 2: Bridging Aerospace and Green Finance

You began your early career as a research scientist in aerospace and computing before becoming a leading global authority on green finance. ***How does your foundational background in "hard engineering" shape how you evaluate the economic viability and investment risk of frontier, large-scale sustainable infrastructure today?***

I spent my early career doing hard sums on things that either worked or exploded, which is a wonderfully clarifying environment for a young scientist or engineer. Aerospace teaches you that a system's real cost is never the one on

the spec sheet , it's the cost of everything that has to go right, in sequence, under uncertainty, for decades. That's a mindset, not a formula, and it's the one I bring to green finance. The long-term. Not surprisingly, in 2005 and inspired by the Long Now project to build a 10,000 year giant clock, Z/Yen founded the Long Finance initiative, commencing research into “when would we know our financial system is working?”.

Most infrastructure investors evaluate frontier projects the way accountants evaluate a bridge: capex, opex, discount rate, done.
Engineers evaluate them the way test pilots do: where does this fail first, how visible is that failure before it happens, and who pays when it does? Green finance for genuinely frontier infrastructure — orbital, deep-sea, polar — needs the second, systems mindset far more than the first. I'd rather underwrite a project with an honest failure-mode analysis and a mediocre IRR than a beautiful spreadsheet with an untested assumption buried in row 40.

Question 3: Funding Mega-Scale Eco-Tourism Infrastructure

As private enterprise accelerates plans for extreme environmental tourism, ranging from deep-sea exploration vessels to orbital commercial hubs like Blue Origin’s *Orbital Reef,* the capital requirements are massive. ***What specific green finance vehicles or bond frameworks do you see as most viable for funding these unprecedented, high-risk infrastructure projects?***

We are entering an era where mega-scale eco-tourism infrastructure resembles venture capital in scale and uncertainty. Traditional project finance alone will not

suffice because early actuarial data is thin to non-existent. Financial structures must accept this reality and feature built-in mechanisms for continuous learning and adaptation. To fund projects like orbital commercial hubs or deep-sea vessels, I see a layered capital framework utilising three primary instruments:

1. Parametric & Catastrophe Structures: Borrowed directly from the reinsurance markets, catastrophe bonds and resilience bonds with parametric triggers are essential. They pay out immediately upon a clearly defined event (such as structural failure, emergency evacuation, or environmental containment breach) rather than forcing operators into prolonged, multiyear claims processes nobody can afford to wait for in extreme environments.

2. Milestone & Performance-Linked Green Bonds: Sustainability Linked Bonds (SLBs) should feature coupon step-downs tied strictly to independently verified engineering milestones, such as the first successful closed-loop resupply or verified zero-discharge cycle, rather than marketing KPIs. Blended finance models, where public or philanthropic capital absorbs first-loss risk, can further catalyse institutional capital by rewarding patient equity while punishing market hype.

3. Integrated Decommissioning Wrappers: Decommissioning linked instruments, such as the SPADRIB/DEDRIB frameworks, must be issued alongside initial construction bonds rather than bolted on as an afterthought when compliance notices an absence of an exit plan.

For the most ambitious projects, I foresee hybrid instruments combining infrastructure debt, venture equity, and insurance wrappers , effectively financialising uncertainty itself. None of these instruments are overly exotic; they represent standard risk-transfer engineering applied to a novel asset class. The overarching rule is transparency: institutional capital will fund calculated risk, but it will never fund opacity.

Question 4: Framing "Victimless Economic Expansion"

You have observed that space exploration uniquely offers a prospect of "mostly victimless economic expansion" compared to historical colonial infrastructure. ***How should frontier infrastructure developers frame the ESG (Environmental, Social, and Governance) narrative to attract institutional investors who want to support pioneering infrastructure without triggering typical ecological backlash?***

Historical colonial infrastructure often had an inherent victim baked directly into its business model, someone’s land, labor, or local resources were expropriated to build a railway, mine, or port. Orbital and deep-ocean frontiers appear low on this original sin: there is no indigenous population in geostationary orbit. On deeper consultation though, the increasing density of objects in orbit does offend indigenous rights to view the sky from New Zealand to Canada’s First Nations, or deep-sea tourism disturbing concepts of areas that should be left alone.

Developers who rely on 'there is nobody here to harm' as their entire narrative present a weak pitch that becomes a hostage to fortune the moment an incident

occurs. Honest framing must centre on demonstrating an active engineering obligation not to create new victims, no orbital debris fields, no seabed devastation, no atmospheric free-riding, no lingering toxic footprint.

Don’t forget that indigenous co-ownership can reduce investment risk, transforming political risk into investment opportunity, when the people of the land are partners in what is built upon it. Indigenous peoples bring something no due diligence process can replicate: generational knowledge of the terrain, the logistics, the supply chains, the community , and the legitimacy that makes approvals stick and projects endure. Including indigenous ownership is not philanthropy; it is superior economics. Economists praise land value capture as a principle , the idea that those who steward land should share in the wealth its development creates. Indigenous coownership is that principle made real. This may apply more to land and sea than space, but I would emphasise mutual structures where needed over purely commercial.

Part II: Policy, Risk Management, & Global "Smart Centres"

Question 5: Policy, Regulation, and Commercial Viability Drawing on your immense experience with the City of London and the London Chamber of Commerce and Industry; ***What role should international policy and commercial centers play in regulating frontier tourism? How do we balance stringent environmental protection standards with the economic incentives needed to attract private developer investment?***

International policy centres and commercial hubs , the City of London , chief among them, earn their keep by doing something governments alone do badly: setting standards that markets then compete to meet rather than merely comply with. My time with the City and the London Chamber of Commerce and Industry taught me that regulation which is only ever a floor gets treated as a floor; regulation that's also a badge of credibility gets treated as a ceiling worth reaching for.

People forget that the vast majority of world trade operates through community-enforced standards markets. International community enforced standards markets support safe, interoperable electrical insulation products across borders, underpinning resilient supply chains and fair market access. At the high end near eco-tourism we see “kitemarks” for good behaviour such as Fairtrade, Rainforest Alliance, or Better Cotton. Ian Harris and I wrote “The Price of Fish” partially based on our work with the Marine Stewardship Council’s kitemark for sustainable wild fisheries.

Frontier tourism needs both a floor (minimum environmental and safety standards, ideally harmonised across the handful of jurisdictions capable of hosting it) and a badge , something like a “frontier tourism kitemark” administered by a commercial centre with genuine credibility, that lets a developer signal quality to investors and insurers without waiting a decade for treaty law to catch up. The balance isn't struck by choosing between environmental stringency and commercial incentive; it's struck by making the stringency itself the commercial incentive.

Question 6: Managing the Liability Profile of "Extreme" Destinations

Commercial tourism in hostile environments, like suborbital flights or deep-sea expeditions, carries inherent, long-tail physical risks. ***As an expert in accounting and financial services, how do you see the global insurance and indemnity markets evolving to effectively underwrite operations where standard actuarial data simply doesn't exist yet?***

Before we get overly lyrical or pan-glossian on “the wonders of markets”, it is important to recognise that we recognise there may be areas, perhaps the Antarctic is a good one where we want to truly leave things alone, reserves, corridors, or set-aside areas where the reserved area increases with the traffic.

However, financial and market solutions to eco-tourism will often be operating in a grey-zone of uncertainty. Insurance markets have solved this problem before, just not in these venues. Lloyd's underwrote the first transatlantic cable and the first commercial flights with essentially no actuarial base either. What happens

is a slow migration from indemnity thinking to parametric thinking: instead of insuring against “what went wrong,” you insure against “did the defined trigger occur,” because the trigger can be specified and priced even when the underlying failure mode can't yet be modelled with confidence.

Expect three things to happen roughly in parallel: syndicated risk pools at Lloyd's and similar markets, because no single underwriter will carry suborbital or deep-sea liability alone in the early years; mandatory, standardised incident-data sharing across operators, because the actuarial base only builds if competitors report failures rather than burying them; and a growing role for mutual structures , operators pooling risk among themselves , because mutuality has always been where insurance goes before the actuarial tables exist to make it a proper market.

The hope is that capital market instruments, such as Insurance Linked Securities (ILS) and captives, will complement traditional insurers. Liability in extreme environments will not be ignored or wished away; it will be diversified, priced transparently, and embedded directly into the balance sheet. I'd back the mutual route hardest; it's how marine insurance itself began.

Question 7: The Role of "Smart Centres" in Driving Infrastructure

Z/Yen’s *Smart Centres Index* tracks the ability of commercial hubs to create, develop, and deploy technology by aligning STEM research with regulatory ecosystems. ***What role can global smart centres play in accelerating the***

commercial deployment of sustainable travel technologies, such as alternative propulsion systems or low-impact architectural engineering?

Z/Yen's Smart Centres Index exists because 'innovative' is a word almost every city claims, yet very few systematically measure. What the index tracks is whether a commercial hub actually connects STEM research talent with a supportive regulatory and financial ecosystem that enables tech to reach commercial scale, two elements people assume happen automatically, but which in practice require deliberate design.

Smart centres accelerate deployment by aligning three core elements: Talent, Technology, and Trust. For frontier sustainable travel technologies, such as alternative hydrogen/electric propulsion, advanced closed-loop systems, or low-impact architectural materials, the bottleneck is rarely research funding; the bottleneck is the time required for regulatory certification and commercial adoption.

Global smart centres accelerate deployment by co-locating research labs with dynamic regulatory sandboxes. This prevents a breakthrough propulsion or materials innovation from sitting idle in an academic lab for eight years while regulatory bodies debate jurisdiction. The commercial hubs that will dominate the next decade are those treating 'fast, safe regulatory iteration' with the same priority as 'fast, safe engineering iteration' , because in frontier infrastructure, they are two sides of the same coin.

Question 8: Framing the Next "State of the Industry" Pivot In your book *The Price of Fish*, you address 'wicked economics' and how we make better long-term decisions for our world. ***If you were to look ahead at the next decade of engineering-themed tourism and infrastructure, what do you consider the single greatest economic or sustainability hurdle the industry must solve to achieve true commercial scale?***

The Price of Fish, was ultimately about one core failure mode: human financial systems are extraordinarily bad at pricing decisions whose costs fall on individuals or ecosystems not present in the room - future generations, distant environments, or unrepresented biomes. One question core to Long Finance has been “how do you fund a forest?”

Jeffrey Sachs points to the discount rate “tyranny of the present over the future” - “If the value of the resource is likely to grow more slowly than the market rate of interest, the blaring market signal is to deplete the resource now and pocket the money! … As expected from the theory, slower-growing animals and plants are especially endangered today.”

Engineering-themed tourism is about to become the purest test case for this 'wicked economics' failure, because its ecosystems are literally distant: low Earth orbit, the deep ocean, or polar ice caps where no local population exists to advocate on their own behalf and the costs are unclear.

The single greatest economic and sustainability hurdle the industry must solve over the next decade is not propulsion, capital, or structural engineering , hard engineering problems always get solved given enough talent and time. The true hurdle is building a genuine, verifiable financial price for harm-at-a-distance before the industry reaches scale, rather than after a catastrophic failure.

Every historic frontier industry , railways, commercial aviation, deep-sea shipping , priced environmental and human harm retrospectively, usually after a disaster forced regulatory intervention. Engineering-themed tourism possesses the unique historical privilege of developing in an era where we already possess the financial tools , performance bonds, parametric triggers, dynamic re-pricing, and mutual risk pools , to price and internalise externalities upfront.

Whether the industry proactively embraces these mechanisms to build long-term capital resilience, or waits for its own high-profile disaster to learn the lesson the hard way, remains the central economic question of our time.

BIOGRAPHY

PROFESSOR MICHAEL MAINELLI KStJ OMRI PhD FCCA FCSI(Hon) FBCS FRSA

Professor Michael Mainelli , is Chairman of Z/Yen Group , President of London Chamber of Commerce , Alderman , City of London and the 695th Lord Mayor of London. Professor Michael Mainelli has published over 60 Journal Articles and 250 Commercial Articles.

OPINION PIECE

OPINION PIECE

ENGINEERING THE COEXISTENCE OF TOURISM AND OIL EXPLORATION INDUSTRIES: A COMPARATIVE CASE STUDY

F.R.I.I. 2026



Figure 1. *Engineering the co-existence of Tourism & Oil Exploration Industries*

ENGINEERING THE COEXISTENCE OF TOURISM AND OIL EXPLORATION INDUSTRIES: A COMPARATIVE CASE STUDY

Journal of Engineering-Themed Environmental Tourism (JETET) ISSN: 2979-1995
Volume 1, Issue 2 (Q3 2026) |
F.R.I.I. (2026)

Abstract

Island nations and coastal economies reliant on heavy extraction and hospitality face a complex socio-technical challenge: balancing dominant, high-impact energy infrastructure with the pristine ecosystems necessary for high-value tourism. This opinion piece evaluates the Republic of Trinidad and Tobago as a dual-industry jurisdiction navigating structural decline in crude output alongside shifting tourism dynamics. By examining peak-to-present production and arrival data, legacy infrastructure decommissioning, and ecological integration, this paper demonstrates that technical engineering mitigations are insufficient without institutional liability frameworks. Ultimately, dual-industry viability requires strict regulatory enforcement, sovereign wealth reinvestment, and mandatory operational halts when environmental containment cannot be guaranteed.

Keywords: *Dual-Industry Coexistence, Energy Transition, Eco-Tourism, Trinidad and Tobago, Coastal Engineering, Environmental Governance, Infrastructure Repurposing.*

1. Introduction & Context

Island nations operating at the intersection of energy extraction and eco-tourism must contend with fundamental spatial, ecological, and economic friction. Historically, energy extraction has provided rapid capital accumulation at the expense of coastal integrity. Conversely, tourism relies on pristine ecosystems, climate stability, and bio-diverse habitats.

In the Republic of Trinidad and Tobago, this balance presents a distinct geographic and economic divide: Trinidad operates as the industrial and petrochemical engine, while Tobago serves as the primary ecological and hospitality haven. Managing both sectors requires a shift from zero-sum resource allocation toward integrated socio-technical planning.

This opinion piece examines a Caribbean jurisdiction operating at distinct stages of energy development: **Republic of Trinidad and Tobago**.. Historical evidence from Trinidad and Tobago, where offshore oil spills have reached vulnerable shorelines, demonstrates that engineering mitigations alone are insufficient without strict institutional accountability. The study highlights how legacy asset adaptation (Trinidad and Tobago) must be coupled with rigorous regulatory enforcement. Ultimately, dual-industry viability requires holding oil exploration majors fully liable for environmental remediation, mandating operational shutdowns whenever effective containment and clean up protocols cannot be guaranteed.



Figure 2. *Map of the Republic of Trinidad &Tobago*

Case Study: Republic of Trinidad and Tobago

2. Macro-Economic Data & Comparative Trajectory

While oil and gas historically dominated Trinidad and Tobago's macro-economy, accounting for roughly 40% of GDP and 80% of export revenues, both energy extraction and tourism have experienced significant volume contraction from their respective historical peaks.

Table 1: Industry Performance Metrics (Peak vs. 2025) Trinidad and Tobago used to be the largest oil producer in the Caribbean, however the sector is now primarily based upon Liquefied Natural Gas LNG and Petrochemical Exports.

Key Industry Performance Data

Metric	Oil Industry (Crude Production)	Tourism Industry (International Arrivals)
Peak Year	2005	2013
Peak Volume	150,000 Barrels Per Day (bpd)	472,585 International Visitor Arrivals
2025 Volume	49,500 Barrels Per Day (bpd)	373,027 International Visitor Arrivals
Net Contraction (%)	-67.0%	-21.1%

Table 1

Data Insights & Sector Vulnerabilities

Oil Sector Decline: Between the 2005 peak and 2025, domestic crude output contracted by 67.0%. The upstream sector has increasingly transitioned toward offshore natural gas and Liquefied Natural Gas (LNG) processing to sustain export earnings.

Tourism Distribution Gap: While total visitor arrivals reached 373,027 in 2025, over 95% of stopover arrivals landed in Trinidad, tied largely to business and industrial travel. Tobago's leisure tourism economy faces acute vulnerability, evidenced by cruise ship calls declining from 41 in the 2024/2025 season to 32 in the 2025/2026 season.

3. Infrastructure Adaptation & Repurposing

The decline in primary crude extraction leaves behind massive onshore and offshore assets, including processing facilities, pipeline networks, marine terminals, and refineries.

Strategic Infrastructure Assessment

A. Asset Decommissioning
B. State Priority vs. Alternative Use
C. Financial Viability of Industrial Eco-Tourism
D. Targeted Environmental Integration
E. Heritage Infrastructure Precedents



Figure 3: *Pointe-a-Pierre Oil Refinery, San Fernando, Trinidad*

Strategic Infrastructure Assessment

A. **Asset Decommissioning**: Major industrial assets have gone offline due to structural shifts in production, most notably the closure of the Pointe-à-Pierre (Guaracara) Refinery in 2018.

B. **State Priority vs. Alternative Use:** Current state strategy prioritizes restarting or leasing offline assets for energy and petrochemical processing rather than large-scale adaptive reuse.

C. **Financial Viability of Industrial Eco-Tourism**: Comprehensive conversion of heavy industrial sites like Pointe-à-Pierre into commercial tourism destinations is capital-prohibitive when compared to traditional greenfield tourism investments.

D. **Targeted Environmental Integration:** Despite financial constraints, selective engineering intersections exist. The Pointe-à-Pierre Wild-Fowl Trust—a premier 30-hectare wildlife reserve and wetland sanctuary situated within the active petrochemical refinery complex—proves that industrial operations and ecological preservation can co-exist when protected zones are strictly managed.

E. **Heritage Infrastructure Precedents:** Industrial adaptation is not without domestic precedent; the conversion of the former Sevillle estate into the Seville Sugar Museum and Heritage Village in Couva illustrates how industrial heritage can be successfully integrated into the national tourism asset base.

4. **Engineering Coexistence: Frameworks for Dual-Industry Viability**

POINT À PIERRE WILDFOWL TRUST PARK



Figure 4 ***P****OINT À PIERRE WILDFOWL TRUST PARK*

To move beyond zero-sum competition for coastal space, public policy must leverage capital from finite extractive sectors to fund renewable tourism infrastructure. Long-term harmony between oil exploration and tourism requires three core institutional mechanisms:

A. **Integrated Coastal Zone Management (ICZM)**

Spatial planning frameworks must establish rigid marine buffer zones. Legally enforced maritime corridors prevent heavy shipping, drilling platforms, and refining effluent from encroaching upon marine protected areas, reef systems, and key beach sites.

B. **Regulatory Liability & Operational Safeguards**

Engineering safeguards are effective only when paired with strict corporate liability. Oil majors operating in coastal waters must be bound by strict legal liability for containment and remediation. Offshore operations must be subject to mandatory operational suspensions if containment, clean-up equipment, or monitoring protocols fail to meet regulatory standards.

C. **Cross-Sector Capital Allocation**

Because fossil fuels are finite and exposed to global energy transition risks, sovereign revenues derived from oil and gas must be systematically ring-fenced. Reinvesting a fixed percentage of energy receipts into green transport grids, coastal defence engineering, and local hospitality training ensures the long-term sustainability of the tourism sector.

5. **Conclusion**

Trinidad and Tobago demonstrates that energy extraction and eco-tourism cannot exist in isolation on small island nations. As fossil fuel assets mature and experience volume declines, the path forward requires active socio-technical integration. By enforcing strict environmental accountability, protecting critical biodiversity hubs like the Pointe-à-Pierre Wild-Fowl Trust, and deploying extractive capital into sustainable tourism infrastructure, island nations can engineering a resilient, dual-industry economy.

.

References

Central Bank of Trinidad and Tobago (CBTT). (2025). Economic Bulletin & Macroeconomic Indicators. Port of Spain: Central Bank of Trinidad and Tobago.

Ministry of Energy and Energy Industries (MEEI). (2025). Consolidated Monthly Crude & Natural Gas Production Reports. Government of the Republic of Trinidad and Tobago.

Ministry of Tourism, Culture and the Arts & Tobago House of Assembly (THA). (2025). Tourism Industry Performance & Visitor Arrival Reports (2013–2025). Scarborough: THA Division of Tourism.

National Trust of Trinidad and Tobago. (2020). Sevilla Great House and Sugar Museum Archives. Heritage Registry, Couva, Trinidad.

Pointe-à-Pierre Wild-Fowl Trust. (2023). Wetland Reserve and Eco-Tourism Operations within Industrial Complexes. Pointe-à-Pierre, Trinidad and Tobago.

Petrotrin / Guaracara Refining Company Limited. (2018). Decommissioning and Asset Restructuring Strategy for the Pointe-à-Pierre Refinery. San Fernando, Trinidad.

Wikipedia Contributors. (2024). "Pointe-à-Pierre Wild Fowl Trust." Wikipedia, The Free Encyclopaedia. Wikimedia Foundation.

Wikipedia Contributors. (2023). "Pointe-à-Pierre Refinery." Wikipedia, The Free Encyclopaedia. Wikimedia Foundation.

Figure Captions

The author(s) would like to acknowledge the use of images from Wikipedia and the use of generative AI tools (Gemini, powered by Google) for creation of conceptual visualizations featured ,produced under strategic direction of **Faith Research & Instruction Institute (FRII).**

Figure 1. *Engineering the co-existence of Tourism & Oil Exploration Industries*
Conceptual visualization of the co-existence of Tourism and Oil Exploration. (Artist's Impression). Created via the Faith Research & Instruction Institute (FRII).

Figure 2. *Map of the Republic of Trinidad &Tobago*

Figure 3: *Pointe-a-Pierre Oil Refinery, San Fernando, Trinidad*

CALL FOR PAPERS

JETET: Official Call for Papers

Journal of Engineering-Themed Environmental Tourism ISSN: 2979-1995



Publisher: Faith Conglomerate Limited

Frequency: Quarterly

Theme: Engineering Resilience in Modern Global Tourism

Volume 1, Issue 3 (Scheduled for Publication ; December 30th , 2026

The Editorial Board of the **Journal of Engineering-Themed Environmental Tourism (JETET)** is pleased to invite researchers, engineers, and practitioners to submit original research, technical notes, and case studies for our upcoming issue. JETET is dedicated to bridging the gap between engineering, environmental conservation, and the expanding global tourism sector.

As Mankind travel capabilities and subsequently travel destinations expand tourism into unprecedented travel experiences and destinations at commercial rates expanding affordability in an upward direction , Issue 3 is highlighting this area of research.

We are specifically seeking contributions within the following pillars:

Pillar 1: Space Tourism

We seek Research papers , Articles , Opinion Pieces on:

- **Low Earth Orbit :** Engineering-Themed Environmental Tourism / Tourism in Low Earth Orbit
- **Futuristic Space Tourism Infrastructure**
- **Artificial Intelligence applications in Engineering-Themed Environmental Tourism / Tourism in Low Earth Orbit and Extra-Terrestrial Locations.**
- **Engineering Eco-Tourism beyond Earth**

Pillar 2: Environmental Protection and Sustainability in Low Earth Orbit and Extra-Terrestrial Areas

We seek Research papers , Articles , Opinion Pieces on:

- **Space Debris**
- **Sustainability beyond Earth**
- **Environmental Stewardship**
- **Environmental Protection beyond Earth**

Pillar 3: Environmental Challenges of Overtourism

As global travel reaches unprecedented densities, infrastructure often exceeds its design life and capacity.

We seek Research papers , Articles , Opinion Pieces on:

- **Infrastructure Strain:** Managing water, waste, and energy systems beyond peak capacity.
- **Structural Mitigation:** Interventions to prevent coastal and ecological degradation in high-traffic zones.

Pillar 4: Reuse Tourism (Adaptive & Circular Engineering)

Repurposing existing structures is a cornerstone of sustainable tourism.

We seek Research papers , Articles , Opinion Pieces on:

- **Industrial Heritage Conversion:** Engineering safety and structural integrity in the adaptive reuse of maritime or industrial sites.
- **Circular Infrastructure:** The use of recycled materials and modular construction in "green" tourism developments.
- **Remediation Strategies:** Transitioning brownfield sites into sustainable public assets.

Pillar 5: Harsh Climes Tourism (Extreme Environment Engineering)

Infrastructure must survive the world's most difficult climates to support emerging tourism markets.

We seek Research papers , Articles , Opinion Pieces on:

- **High-Salinity Environments:** Material durability and corrosion resistance in coastal engineering.
- **Arid & Arctic Logistics:** Sustainable HVAC, water harvesting, and low-impact foundations for desert or tundra environments.

Submission Guidelines

- **Abstracts:** 250–300 words outlining the problem, methodology, and results.
- **Format:** Submissions should follow IEEE or APA citation standards.
- **Review Process:** All submissions undergo a double-blind peer review managed by the Faith Research and Instruction Institute.
- **Open Access:** JETET is an open-access journal; all published works will receive a permanent DOI via Zenodo.

Important Dates

- **Abstract Submission Deadline:** October 30th , 2026
- **Full Manuscript Deadline:** November 30th , 2026
- **Publication Targeted Date:** December 30th , 2026

How to Submit: Please send your abstracts or inquiries directly to the Editor-in-Chief at **info@fcl-uk.com** or submit via the official JETET Zenodo Community portal at **10.5281/zenodo.19563234** .

How to Cite JETET

1. To Cite the Entire Issue

Faith Conglomerate Limited. (2026). *Journal of Engineering-Themed Environmental Tourism (JETET)*, Vol. 1, No. 1. https://doi.org/10.5281/zenodo.19563234

2. To Cite an Individual Article (Example)

[Author Name]. (2026). " Engineering and Sustainable Tourism: A Conceptual Framework for SIDS." *Journal of Engineering-Themed Environmental Tourism (JETET)*, 1(1), pp. 1-15. Faith Conglomerate Limited. https://doi.org/10.5281/zenodo.19563234

Sponsorship & Partnership

Sponsorship & Partnership

Founding Sponsor

Journal of Engineering-Themed Environmental Tourism (JETET) is proud to be supported by its founding sponsor, **Faith Conglomerate Limited (FCL)**.

Faith Conglomerate Limited provides the essential infrastructural, financial, and administrative support required to maintain JETET as a premier, open-access platform. Through this partnership, FCL enables the **Faith Research & Instruction Institute (FRII)** to disseminate high-level engineering research and visionary perspectives on the experience economy without financial barriers to authors or readers.

Strategic Partners

JETET collaborates with global entities to bridge the gap between theoretical engineering and practical tourism applications. Our current partnership network includes:

- **Faith Research & Instruction Institute (FRII):** Leading the peer-review process and academic standards for all technical submissions.
- **Zenodo / CERN:** Providing permanent Digital Object Identifiers (DOIs) and long-term digital archiving for all published works.

Call for Partnerships: Volume 1, Issue 3

As we look toward our next issue (January , 2027), JETET invites inquiries for strategic partnerships from:

- **Academic Institutions:** Seeking to showcase research in Civil, Environmental, or Astronautical Engineering.
- **Commercial Aerospace & Engineering Firms:** Interested in contributing case studies or industrial perspectives.
- **Environmental Agencies:** Focused on land remediation and sustainable habitat development.
- **Eco-Tourism Resorts &,Industry**
- **The Environmental Sustainability Industry**
- **The Tourism Industry**

To discuss partnership opportunities, sponsorship tiers, or collaborative research initiatives, please contact our Editorial Office:

Email: info@fcl-uk.com

LinkedIn: Join the JETET Group


Journal of
Engineering-Themed
Environmental Tourism



SUSTAINABILITY IN TOURISM . Earth Walks Club

ISSN 2979-1995

Journal of Engineering-Themed Environmental Tourism

